



F SERIES

SINGLE-PHASE **INVERTER**



HIGH PERFORMANCE

Low start-up voltage, wide voltage range, 97.4% maximum efficiency.



EASY INSTALLATION

Flexible configuration, plug and play set-up.



IP65 RATED

Engineered to last with maximum flexibility. Suitable for outdoor installation.



REMOTE MONITORING

Monitor your system remotely via smartphone app or web portal.



Advanced System Monitoring
with **FoxCloud V2.0**

REFINED – POWERFUL – FLEXIBLE

Fox ESS offers a range of single and dual-MPPT single-phase inverter offering unparalleled efficiency and performance. Our dual-MPPT F Series range includes 3 – 6kW models. The F Series is IP65 rated and battery ready for easy upgrade when paired with a Fox ESS charge controller.

3kW ...>> 6kW



For more about the Fox ESS range of single-phase inverters, visit:

www.fox-ess.com



TECHNICAL SPECIFICATIONS

MODEL	F3000	F3600	F4600	F5000	F5300	F6000
INPUT(PV)						
Max. Input Power [W]	3900	4680	5980	6500	6890	7800
Max. Input Voltage [V]			600			
Start-up Input Voltage [V]			120			
Rated Input Voltage [V]			360			
MPPT Operating Voltage Range [V]			80 ~ 550			
Max. Input Current[A]			12.5			
Max. Short-circuit Current [A]			15			
No. of Independent MPP Trackers			2			
No. of Strings per MPP Tracker			1			
OUTPUT(AC)						
Rated Output Apparent Power [VA]	3000	3600	4600	5000	5300	6000
Max. Output Apparent Power [VA]	3300	3960	5060	5500	5830	6000
Rated Grid Voltage [Vac]			220/ 230/ 240			
Rated Grid Frequency [Hz]			50/ 60			
Rated Output Current [A]	13.0	15.7	20.0	21.7	23.0	26.1
Max. Output Current [A]	14.3	17.2	22.0	23.9	25.3	26.1
Power Factor	1 (Adjustable from 0.8 leading to 0.8 lagging)					
Total Harmonic Distortion (THDi) [%]	<3					
EFFICIENCY						
MPPT Efficiency [%]	99.00					
Euro-efficiency [%]	96.80					
Max. Efficiency [%]	97.40					
PROTECTION						
Insulation Monitoring	YES					
Residual Current Monitoring	YES					
DC Reverse Polarity Protection	YES					
Anti-islanding Protection	YES					
AC Short-circuit Protection	YES					
AC Overcurrent Protection	YES					
AC Overvoltage Protection	YES					
Surge Protection	Optional (DC/AC: Type II)					
DC Switch	Optional					
GENERAL DATA						
Dimensions (W*H*D) [mm]	402*476.5*148					
Weight [kg]	15.5					
Cooling Method	Natural Convection					
Topology	Transformerless					
Noise Emission (typical) [dB]	<30					
Max. Operating Altitude [m]	3000					
Operating Temperature Range [°C]	-25 ~ 60					
Humidity [%]	0 ~ 100 (No Condensation)					
Ingress Protection	IP65					
Internal Consumption at Night [W]	<1					
Monitoring Module	LAN/ WIFI / GPRS / 4G (Optional)					
Communication	RS485, Meter / CT, DRM					
Display	LCD, Touch Key, App, Website					
STANDARD COMPLIANCE (MORE AVAILABLE UPON REQUEST)						
Safety	EN/IEC 62109-1/2, BIS IS 16169, BIS IS 16221-1/2					
EMC	EN 61000-6-1/2/3/4					
Grid Regulation	AS/NZS-4777.2, ABNT NBR 16149, ABNT NBR 16150, C10/11, EN 50549-1, PN EN-50549-1, VDE-AR- N4105, VDE V 0126-1-1, UTE C 15-712-1,TAI-PEA, TAI-MEA, RD 1699, CEI 0-21, IEC 61727, IEC 62116, IEC 61683, IEC 60068-2-1/2/14/30/64, G98, G99					